

2mm - 10mm 3D Wire Bending Machine 380V Wire Processing Machine

Basic Information

Place of Origin: Guangdong, ChinaBrand Name: Jin Hongxiang

Certification: CE
Model Number: JX3D2-8
Minimum Order Quantity: 1 set
Price: consult

Packaging Details: Export wooden caseDelivery Time: 5-10 days or negotiation

Payment Terms: L/C, T/T

Supply Ability: 20 Set/Sets per Month



Product Specification

Product Name: 3D Wire Bending Machine

Machine Type:3E

Control System: PLC+servo

Applicable Industries: Hardware, wire Processing

• Warranty Of Core 1 Year

Components:

Wire Size: ø2-10mmNo. Of Axis: 7 Axis

• Highlight: 3D Wire Bending Machine

AutomaticPort: Automatic

• Highlight: 2mm 3D Wire Bending Machine,

10mm 3D Wire Bending Machine, 380V Wire Processing Machine



3D Wire Bending Machine 2-10MM

This 3D molding machine is for iron wire with a diameter of 2-10mm

The biggest feature of this machine is that the iron wire rotates and the head is fixed

Performance characteristics

- 1. The computer starts and shuts down quickly, and the operation is simple and convenient. The computer interface can change the program while adjusting speed while producing.
- 2. High brand high-speed motor and reducer are used in configuration, and the production speed is more than 25% higher than that of similar products in domestic peers.
- 3. The production can realize that the angle does not change at the slowest angle, and the production stability is better.
- 4. Bearings, gears and other important parts are imported brand accessories, with a 365 day warranty, and the equipment is durable and reliable
- 5. With high precision, it can be used for wire rod forming products in the range of 2.0-10 mm wire diameter, and the error is reduced to 0.1 mm
- 6. The matching use of steel wire butt joint machine makes the wire change operation of the machine more convenient.
- 7. It can be connected to the Internet and WiFi through mobile phone or computer to realize remote control, which makes after-sales service more convenient.

Technical Parameters

| Model | JX3D-6 | JX3D-8 | JX3D-10 | |
|--------------------------------|-------------------------|-------------------------------------|-------------------------|--|
| No. of axis | 380V,7 axis | 380V,7 axis | 380V,7 axis | |
| Machining wire diameter(MM) | l | Hard material Φ3.0 Φ6.0 | | |
| | Soft material Ф2.0 Ф6.0 | Soft material Φ 3.0 Φ 8.0 | Soft materialΦ3.0 Φ10.0 | |
| Number of wire feeding wheels | 3 groups | 3 groups | 3 groups | |
| Spool servo motor (KW) | 2 | 2.7 | 4.5 | |
| Head shaft servo motor (KW) | 2 | 2.7 | 4.5 | |
| Cutter shaft servo motor(KW) | 1 | 1 | 2 | |
| Lifting shaft servo motor (KW) | 1 | 1 | 2 | |
| Angle axis servo motor (KW) | 1 | 1 | 1 | |
| Machine size (MM) | 3800X1860X1660 | 3800X1860X1660 | 3800X1860X1660 | |

3D bending product display



Dongguan Jinghongxiang Automation Equipment Co., Ltd.

13925780098

jhx16888@gmail.com

wire-bendingmachine.com

No. 78, Shangzhong Road, Shangdi Industrial Zone, Liaobu Town, Dongguan, Guangdong, China